



PATENT ABSTRACTS OF JAPAN

(11) Publication number: 08189870 A

(43) Date of publication of application: 23.07.1996

(51) Int. Cl. G01L 9/12
H01L 29/84

(21) Application number: 07001525

(22) Date of filing: 09.01.1995

(71) Applicant: NAGANO KEIKI SEISAKUSHO LTD

(72) Inventor: YOKOYAMA SEIICHI
ITO KOJI
KAIZE FUMIO

(54) PRESSURE SENSOR

(57) Abstract:

PURPOSE: To measure the pressure accurately even under a high humidity by coupling a molecule having a hydrophobic radical with a molecule or atom which constitutes the exposed surface of insulative members forming a gap with respect to a diaphragm.

CONSTITUTION: A diaphragm 1 consisting of a certain material, for example mono-crystal silicon, is joined with a pair of insulative members 2, 2' oppositely positioned in a large wall thickness part 1a. Thereby, the diaphragm 1 is pinched by the insulative members 2, 2' in the state that a gap is formed between the diaphragm and the members 2, 2' at a flat plate part 1b. A lead-in hole 4 for measuring pressure is formed in the gap in the members 2, while another

lead-in hole 5 for a reference pressure, for example the atmospheric pressure, for comparison with the measuring pressure is formed in the other member 2'. A molecule having a hydrophobic radical is coupled with at least a part of a molecules or atoms which constitute the exposed surface of each insulative member 2, 2' in the gap, and thereby, these surfaces are equipped with water repellency. One example of such a molecule having hydrophobic radical is a silane coupling agent.

COPYRIGHT: (C)1996,JPO

